

# SONALIKA - 26



**POWERED  
TO  
PERFORM**

	Specifications	SONALIKA - 26
<b>Engine</b>	Engine Type HP Category No. of Cylinders Aspiration Cubic Capacity (cc) Rated RPM (+/-25mm) Air cleaner Cold Start Max Torque @ RPM(Nm) Exhaust	3 cylinder, Mitsubishi S3L2,4,water cooled, vertical overhead valve, in line swirl chamber type 26 HP 3 Naturally Aspirated 1318cc 2700 Dry type Yes 75.2@2200 Underhood Downdraft silencer
<b>Transmission</b>	Drive Clutch Gearbox Front Axle Transmission	4WD Single clutch Sliding mesh 4 WD 6F+2R
<b>Speed (Forward)</b>	Maximum Speed (Km/Hr) Minimum Speed (Km/Hr)	17.05 1.53
<b>Brakes</b>	Brakes Type of actuation Trailer Brake Hand brake	OIB Mechanically actuated No Yes, Latch Type
<b>Differential lock</b>	Differential lock	Yes, Foot Operated
<b>PTO</b>	PTO (rpm) PTO (actuation)	540 @ 2080 ERPM , 540 E @ 1410ERPM, 1000 @ 1514ERPM Mechanically actuated
<b>Steering</b>	Steering	Power steering
<b>Electrical</b>	Battery Alternator Seven pin trailer socket	12V,50A 12V,40A Yes
<b>Hydraulics</b>	3 point linkage Stay Bars Hydraulic lifting capacity Auxiliary hydraulic circuit Liftomatic Lift rods	Yes , Cat-1N No, available with anchor chains 600Kg 1DA No Adjustable lift rods
<b>Safety Switch</b>	Clutch Safety Switch PTO Safety Switch Neutral safety switch	Yes No No
<b>Capacity (ltrs)(+/-5%) approx</b>	Fuel tank (Lt) Engine Oil (Lt)	30lts 4.2lts
<b>Turning Diameter</b>	Turning diameter With Brakes (m) Turning diameter Without Brakes(m)	5.54 6.35
<b>Tyre</b>	Front Rear	6-12 8.3-20
<b>Dimension &amp; Weight(+/-5%)</b>	Weight (kg) Wheel Base (mm) Total Length (mm) Total Width (mm) Height (mm) Min Ground Clearance (mm) min Front Track (mm) Rear Track (mm)	1055Kg 1560mm 2705mm 1058mm 2153mm with ROPS 225mm (Front axle lower pt) 894mm 825mm
<b>Others</b>	Fuel Indicator gauge Front Toe Hook Front weight Trailer hitch ROPS FOPS Drawbar	Yes Yes Front wts- (15x2) Fixed Trailer Hitch Yes, E-Marked with detachable Beacon light No Yes
<b>Optional Features</b>	Optional Tyres	1. Agriculture tyres: Front tyre: 6-12 Rear tyre: 8.3-20 2. Turf tyres: Front tyre: 23x8.50-12LG 306 12PR TL Rear tyre-33x15.50-16.5 LG 306 10PR TL 3. Industrial tyres: Front tyre-23x8.50-12 SPHD 12PR TL Rear tyre-31x15.50-15 SPHD10 PR TL
	Cabin	Heater only

## International Tractors Limited

H.O: Plot No. 29 and 31, Aggarwal Mall, CBD Ground, Near Karkardooma Court,  
Behind Hotel Kempinski, Delhi-110032 (India). **Phone:** +91 11 22600700, Fax: +91 11 22377472  
**Works:** Jalandhar Road, Hoshiarpur-146022, Punjab (India). **Phone:** +91 1882 302220, 302221,  
**Fax:** +91 1882 302293, **E-mail:** exports@sonalika.com , **Website:** www.sonalika.com.

Follow us on [www.facebook.com/SonalikaTractor](https://www.facebook.com/SonalikaTractor) | [www.twitter.com/SonalikaTractor](https://www.twitter.com/SonalikaTractor) | [www.linkedin.com/groups/Sonalika-Tractor](https://www.linkedin.com/groups/Sonalika-Tractor)